

Table 5-- Product information sheet	
Type of light source	
Lighting technology used	<input type="checkbox"/> HL <input type="checkbox"/> LFL T5 HE <input type="checkbox"/> LFL T5 HO <input type="checkbox"/> CFLni <input type="checkbox"/> other FL <input type="checkbox"/> HPS <input type="checkbox"/> MH <input type="checkbox"/> other HID <input checked="" type="checkbox"/> LED <input type="checkbox"/> OLED <input type="checkbox"/> mixed <input type="checkbox"/> other
Non-directional or directional	<input checked="" type="checkbox"/> Directional <input type="checkbox"/> Non-directional
Light source cap-type (or other electric interface)	Integrated
Mains or non-mains	<input checked="" type="checkbox"/> Mains <input type="checkbox"/> Non-mains
Connected light source (CLS)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Colour-tuneable light source	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Envelope (other HID)	<input checked="" type="checkbox"/> No <input type="checkbox"/> Second <input type="checkbox"/> Non-clear <input type="checkbox"/> Second + Non-clear
High luminance light source:	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Anti-glare shield	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Dimmable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Only with specific dimmers
General product parameters	
Parameters	Input: 200-240V~, 50/60Hz, 0.8A Max Output: DC12V, 2A
Energy consumption in on-mode (kWh/1000h)	24
Energy efficiency class	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input type="checkbox"/> E <input checked="" type="checkbox"/> F <input type="checkbox"/> G
Useful luminous flux (lm)	2000
Beam angle correspondence	<input type="checkbox"/> Sphere (360°) <input checked="" type="checkbox"/> Wide cone (120°) <input type="checkbox"/> Narrow cone (90°)
Correlated colour temperature type	<input type="checkbox"/> Single value <input type="checkbox"/> Range <input checked="" type="checkbox"/> Steps
Correlated colour temperature (K)	3000K, 4000K, 4500K, 5000K, 6000K
On-mode power (W)	23.88
Standby power (W)	0.38
Networked standby power for CLS (W)	-
Colour rendering index	92
Colour rendering index range (Minimum)	92
Colour rendering index range (Maximum)	92
Outer dimensions (Height) (millimetre)	-
Outer dimensions (Width) (millimetre)	-
Outer dimensions (Depth) (millimetre)	-
Claim of equivalent power	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> Not applicable
Equivalent power (W)	-

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: +86 755-29116082 Web: www.hx-lab.com

Chromaticity coordinates (x)	0.425
Chromaticity coordinates (y)	0.391
Parameters for directional light sources	
Peak luminous intensity (cd)	626
Beam angle (degrees)	120
Beam angle (degrees) (Minimum)	120
Beam angle (degrees) (Maximum)	120
Parameters for LED and OLED light sources	
R9 colour rendering index	52
Survival factor	1
Lumen maintenance factor	0.97
Parameters for LED and OLED mains light sources	
Displacement factor	0.95
Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> Not applicable
Replacement claim (W)	-
Flicker metric	0.1
Stroboscopic effect metric	0.1